



## PRINCIPLE Nitrile Gloves

**TECHNICAL DATASHEET** 



Integrity Cleanroom PRINCIPLE Nitrile Gloves are ambidextrous, with a beaded cuff which has been designed for extra protection. The textured surface and enhanced grip makes these nitrile gloves ideal for handling delicate items.

Our gloves are powder and latex free, assisting in reducing the risk of an allergic reaction.



## **FEATURES**

- Class 100/ISO 5
- 100% Nitrile Butadiene Rubber
- Length: 305mm / 12 inch
- · Powder free and latex free
- Beaded cuff with textured fingers
- White
- 5 year shelf life from manufacture

| PRODUCT CODE | DESCRIPTION                         | SIZE | LENGTH (INCH) | QUANTITY     |
|--------------|-------------------------------------|------|---------------|--------------|
| 602-0410     | PRINCIPLE Non-Sterile Nitrile Glove | S    | 12            | 100 pcs/pack |
| 602-0411     | PRINCIPLE Non-Sterile Nitrile Glove | M    | 12            | 100 pcs/pack |
| 602-0412     | PRINCIPLE Non-Sterile Nitrile Glove | L    | 12            | 100 pcs/pack |
| 602-0413     | PRINCIPLE Non-Sterile Nitrile Glove | XL   | 12            | 100 pcs/pack |

## **SPECIFICATIONS**

| PROPERTIES          | RESULT   |  |  |
|---------------------|--|--|--|
| Surface             | Finger textured  |  |  |
| Colour              | White  |  |  |
| Length              | 305mm / 12 inch  |  |  |
| Thickness           | 5.0 mil (±1)   |  |  |
| Tensile strength    | Min 15 Mpa   |  |  |
| Elongation          | 600%   |  |  |
| Packing style       | 100 pcs per bag   10 bags per carton (1000 pcs in total)   |  |  |
| Physical Properties | Meets the requirements of the Glove Standard EN420:2003+A1:2009 and the European Medical Gloves Standard EN455 (Parts 1, 2, 3, 4) & EN374-:2016 (Part 1, 2, 3, 4 and 5). Product fulfils the cleanroom specifications of nitrile gloves as per ISO 23464:2020. |  |  |
| AQL                 | AQL 1.5  |  |  |

To request a quotation or for more information, please call +44 (0)1473 836205 email info@integritycleanroom.co.uk or visit www.integritycleanroom.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © 2025 Integrity Cleanroom.



## CONTD.

| PROPERTIES  | RESULT  |  |  |
|---|---|--|--|
| Material  | 100% Nitrile Butadiene Rubber   |  |  |
| Shelf life  | Five (5) years from date of manufacture   |  |  |
| Storage instructions                                    | Store in a cool dry place (< 40°C) away from direct light sources   |  |  |
| Batch Traceability                                      | The traceability numbers are shown on the sealed inner PE bag and the carton  |  |  |
| Liquid Particle Counts (as determined by IES-RP-C005.4) | < 1200 particle counts cumulative at 0.5micron  |  |  |
| Organics<br>(IES-RP-CC005.4)                            | Silicone Oil Free, detected by FTIR Spectroscopy  |  |  |
| Non-Volatile Residue                                    | <10 microgram/ sq. cm   |  |  |
| ESD Parameters (ASTM D-257)                             | Surface Resistance - ≤10E10 Ohms/sq.<br>Decay Time (Sec) - ≤0.5<br>Tribo Charge (Volts) - ≤20                               |  |  |
|   | Length: 305 ± 10 mm<br>Palm Width: 80-89 to 110-116 mm  |  |  |
| Dimension Criteria                                      | Single Wall thickness: Finger thickness: $0.13\pm0.03$ mm Palm thickness: $0.10\pm0.02$ mm Cuff thickness: $0.06\pm0.02$ mm |  |  |

| Ionic Burden (microgram/ sq cm) (as determined by IES-RP-C005.4)        |   |  |  |  |  |
|---|---|--|--|--|--|
| Fluoride <0.030<br>Chloride <1.200<br>Phosphate <0.800<br>Sodium <0.050 | Sulphate <0.800<br>Nitrate <1.000<br>Bromide <0.050<br>Magnesium <0.004<br>Potassium <0.050 |  |  |  |  |

To request a quotation or for more information, please call +44 (0)1473 836205 email info@integritycleanroom.co.uk or visit www.integritycleanroom.co.uk

IMPORTANT: This data sheet and its contents (the "Information") belong to Integrity Cleanroom or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but Integrity Cleanroom assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where Integrity Cleanroom was aware of the possibility of such loss or damage arising) is excluded. © 2025 Integrity Cleanroom.